



OUTLANDER™ 1000

XT model shown.



OUTLANDER 1000



OUTLANDER 1000 XT™

SPECIFICATIONS

ENGINE	
Type	976cc, V-twin, liquid-cooled, SOHC, 8-valve (4-valve/cyl)
Bore & Stroke	91 x 75 mm
EFI System/Carburetor	46 mm Throttle Body, 2 Siemens™ VDO injectors
Starting System	Electric
Transmission	CVT, sub-transmission with high, low, park, neutral & reverse. Standard engine braking
Drive Train	Selectable 2w/4w shaft driven with Visco-Lok ¹ front differential

CHASSIS	
Frame	SST G2
Front Suspension Type/Shocks	Double A-arm
Front Suspension Travel	9 in (229 mm)
Rear Suspension Type/Shocks	Torsional Trailing arm Independent (TTI)
Rear Suspension Travel	9.3 in (236 mm)
Front Brake	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear Brake	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper
Tires/Front	26 x 8 x 12 in 660 x 203 x 305 mm
Tires/Rear	26 x 10 x 12 in 660 x 254 x 305 mm
Wheels	Cast-aluminum

DIMENSIONS	
L x W x H (in)	86 x 46 x 44 in
L x W x H (mm)	2,184 x 1,168 x 1,118 mm
Wheelbase	51 in (1,295 mm)
Seat Height	34.5 in (877 mm)
Ground Clearance	12 in (305 mm)
Dry Weight	747 lb (339 kg)
Towing Capacity	1,300 lb (590 kg)
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)
Storage	Rear: 5.7 US gal (21.4L)
Fuel Capacity	5.4 US gal (20.5L)

FEATURES	
Instrumentation	Multi-function digital LCD gauge: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock, auto shut off after 15 minutes
Anti-theft System	D.E.S.S.™ (Digital Encoded Security System)
Electrical	Prewired for winch
Lighting	230-watt front twin 60-watt projectors and dual 55-watt reflectors with tail light/brake light
DC Outlet	Lighter type in console, standard connector in the back (15A)
Color Available	Viper Red ■

WARRANTY	
Basic	6 months limited factory warranty
Extended	B.E.S.T. available from 12 to 36 months

XT PACKAGE

- Tri-mode Dynamic Power Steering (DPS™)
- Visco-Lok QE
- Cast-aluminum wheel with machined finish
- 26-inch Carlisle™ ACT radial tires
- 3000-pound WARN™ winch with roller fairlead, wired remote control & integrated remote storage
- Heavy-duty front & rear bumpers
- Handlebar with wind deflectors
- 650-watt magneto
- Industry-exclusive NEXT G-1 Vista™ Camo color option
- NEW Pure Magnesium Metallic painted plastics color option
- Colors: Black ■
Yellow ■
Camo ■
Pure Magnesium Metallic ■

BEST PROTECTION ©2011 Bombardier Recreational Products, Inc. (BRP). All rights reserved.™ and the BRP logo are registered trademarks of BRP or its affiliates. Visco-Lok is a trademark of CNX Visco-Lok GmbH. All other trademarks are the property of their respective owners. Products are distributed in the USA by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S., call the ATV Safety Institute at 1 (800) 887-2867. In Canada, call the Canadian Safety Council at 1 (613) 734-1535 ext 222. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol/drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

