



X xc model shown.



RENEGADE 1000



RENEGADE 1000 X™ xc

SPECIFICATIONS

ENGINE

Type	976cc, V-twin, liquid-cooled, SOHC, 8-valve (4-valve/cyl)
Bore & Stroke	91 x 75 mm
EFI System/Carburetor	46 mm Throttle Body, 2 Siemens™ VDO injectors
Starting System	Electric
Transmission	CVT, sub-transmission with high, low, park, neutral & reverse. Standard engine braking
Drive Train	Selectable 2w/4w shaft driven with Visco-Lok ¹ front differential

CHASSIS

Frame	SST G2
Front Suspension Type/Shocks	Double A-arm/ FOX Racing Shox [®] HPG shocks
Front Suspension Travel	9 in (229 mm)
Rear Suspension Type/Shocks	Torsional Trailing arm Independent (TTI)/FOX Racing Shox HPG shocks
Rear Suspension Travel	9.3 in (236 mm)
Front Brake	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear Brake	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Tires/Front	ITP Holeshot [™] ATR 25 x 8 x 12 in 635 x 203 x 305 mm
Tires/Rear	ITP Holeshot ATR 25 x 10 x 12 in 635 x 254 x 305 mm
Wheels	Cast-aluminum

DIMENSIONS

L x W x H (in)	86 x 46 x 45 in
L x W x H (mm)	2,184 x 1,168 x 1,143 mm
Wheelbase	51 in (1,295 mm)
Seat Height	34.5 in (877 mm)
Ground Clearance	12 in (305 mm)
Dry Weight	687 lb (312 kg)
Towing Capacity	1,300 lb (590 kg)
Rack Capacity	35 lb (16 kg)
Fuel Capacity	5.4 US gal (20.5L)

FEATURES

Instrumentation	Multi-function gauge: Speedometer, tachometer, odometer, trip and hourmeters, fuel, gear position, 4 x 4 indicator, diagnostics, clock, auto shut off
Anti-theft System	D.E.S.S. [™] (Digital Encoded Security System)
Electrical	Prewired for winch
Lighting	4 fender mounted projector beam headlamps (60W) with tail light/brake light
DC Outlet	Lighter type in console, standard connector in the back (15A)
Color Available	Yellow ■

WARRANTY

Basic	6 months limited factory warranty
Extended	B.E.S.T. available from 12 to 36 months

X xc PACKAGE

- Tri-mode Dynamic Power Steering (DPS[™])
- Visco-Lok QE
- NEW Aluminum beadlock wheels
- Front and rear FOX Racing Shox HPG piggyback shocks with dual-speed compression, rebound & preload adjustments
- Aluminum skid plate
- Handlebar wind deflectors
- Aluminum taper-profile handlebar with square pad
- 650-watt magneto
- X xc package coloration, graphics & seat cover
- Color: Yellow & Black with X package graphics ■

BEST PROTECTION ©2011 Bombardier Recreational Products Inc. (BRP). All rights reserved. [™] and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. Visco-Lok is a trademark of GKN Viscotek GmbH. [®] All other trademarks are the property of their respective owners. Products are distributed in the USA by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or in U.S., call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol/drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 50cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

can-am

