



**RENEGADE™ 500**



**RENEGADE 500**



**SPECIFICATIONS**

ENGINE	
Type	499.6cc, V-twin, liquid-cooled, SOHC, 8-valve (4-valve/cyl)
Bore & Stroke	82 x 47 mm
EFI System/Carburetor	46 mm Throttle Body, 2 Siemens™ VDO injectors
Starting System	Electric
Transmission	CVT, sub-transmission with high, low, park, neutral & reverse. Standard engine braking
Drive Train	Selectable 2w/4w shaft driven with Visco-Lok <sup>1</sup> front differential

CHASSIS	
Frame	SST
Front Suspension Type/Shocks	RS-Type Double A-arm/ Motion Control shocks
Front Suspension Travel	8.5 in (216 mm)
Rear Suspension Type/Shocks	RS-Type Torsional Trailing arm Independent (TTI)/ Motion Control shocks
Rear Suspension Travel	9 in (229 mm)
Front Brake	2 hydraulic discs
Rear Brake	1 inboard hydraulic disc
Tires/Front	ITP Holeshot™ ATR 25 x 8 x 12 in 635 x 203 x 305 mm
Tires/Rear	ITP Holeshot ATR 25 x 10 x 12 in 635 x 254 x 305 mm
Wheels	Center-cast aluminum

DIMENSIONS	
L x W x H (in)	86 x 46 x 45 in
L x W x H (mm)	2,184 x 1,168 x 1,143 mm
Wheelbase	51 in (1,295 mm)
Seat Height	34.5 in (877 mm)
Ground Clearance	11 in (279 mm)
Dry Weight	614 lb (279 kg)
Towing Capacity	1,300 lb (590 kg)
Rack Capacity	35 lb (16 kg)
Storage	Rear: 1 US gal (3.7L)
Fuel Capacity	4.3 US gal (16.3L)

FEATURES	
Instrumentation	Multi-function gauge: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock, auto shut off
Anti-theft System	D.E.S.S. <sup>™</sup> (Digital Encoded Security System)
Electrical	Prewired for winch
Lighting	4 fender mounted projector beam headlamps (60W) with tail light/ brake light
DC Outlet	Lighter type in console, standard connector in the back (15A)
Colors Available	Yellow <input checked="" type="checkbox"/> White <input type="checkbox"/>

WARRANTY	
Basic	6 months limited factory warranty
Extended	B.E.S.T. available from 12 to 36 months

**BEST PROTECTION** ©2011 Bombardier Recreational Products, Inc. (BRP). All rights reserved. <sup>™</sup> and the BRP logo are registered trademarks of BRP or its affiliates. <sup>™</sup>Visco-Lok is a trademark of CNX Visco-Lok GmbH. <sup>®</sup>All other trademarks are the property of their respective owners. Products are distributed in the USA by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S. call the ATV Safety Institute at 1 (800) 687-2867. In Canada, call the Canadian Safety Council at 1 (613) 734-1535 ext 222. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol/drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

